

AQUA THERM

HOT WATER PARTS WASHER ADDITIVE

ADITIVO PARA LAVAR LAS PARTES EN AGUA CALIENTE

READ ENTIRE LABEL BEFORE USING. KEEP OUT OF REACH OF CHILDREN

SAFETY SECTION



TOXICITY 1
FIRE 1
REACTIVITY 1
SPECIAL NVA

WARNING

- SKIN AND EYE IRRITANT
- RESPIRATORY TRACT IRRITANT
 SWALLOWING WILL CAUSE GASTRO-INTESTINAL IRRITATION



Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent; cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water

for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediatly. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

Ingredient Name	CAS#
Triethanolamine	102-71-6
Alkylbenzene sulfonic acid	68584-22-5
Diethylene glycol	111-46-6
Diethanolamine	111-42-2
Mono-ethyl ether	111-90-0
Linear AlkIbenezene Sulfonate Acid	68584-22-5
TSP	7601-54-9



WARNING: This product can expose you to chemicals including Diethanolamine, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

PRODUCT #2085 • BATCH #

TO REORDER CALL US @ 800.648.1153

AQUA THERM has been designed as an additive for use in all hot and warm water circulating parts washers. It is ideal for both ferrous and non-ferrous metals. The blending of detergents, solvents and emulsifying compounds in AQUA THERM enables it to penetrate the most difficult oil and grease-bearing soils. The addition of high-tech surfactants reduces surface tension on major soils, allowing the compound to penetrate the target soil and lift it from the surface. AQUA THERM is a nearly neutral pH with very low vapor emission, even under a heated condition. The addition of this compound to your aqueous based parts cleaner will save time and money with reduced; cleaning time, ease of use, safety and economy of dilution.

DIRECTIONS

AQUA THERM is not designed for use in Mart Washers or other high-velocity cabinet washers. Use AQUA THERM straight. The optimum working temperature range is between 100°Fand 190°F. Parts left in direct sunlight for 30 minutes to an hour, prior to immersion in your parts washer, will strip at a faster rate. Always pre-heat your solution prior to parts immersion. Always remove heavy grease/dirt deposits with a putly knife prior to immersion. This practice will expedite the cleaning process as well as increase the longevity of your cleaning solution. AQUA THERM contains corrosion inhibitors. However, in some cases, some metals will oxidize shortly after being stripped by this or any other product. We recommend the use of one of Sunrise's anti-corrosion coatings if oxidation is present. Consult your Sunrise Representative for the proper compound.

CAUTION

USE VENTILATION ADEQUATE TO MAINTAIN TLV. AVOID CONTAMINATION OF FOOD OR POTABLE WATER. DO NOT INGEST. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

SHIPPING/ DOT CLASSIFICATION

LIQUID CLEANER CLASS 55

SUNRISE ENVIRONMENTAL SCIENTIFIC



800-648-1153 SUNRISENV.COM PO BOX 10207 - RENO, NEVADA 89510