


TRANSFORM IS THE ANSWER!!!

EFFICIENCY - % of weight picked up

DESCRIPTION		Closest Competitor 1	Closest Competitor 2	Closest Competitor 3
Motor oil	638%	464%	300%	283%
Paint (Latex-Flat)	1100%	943%	550%	550%
Power steering fluid	717%	614%	331%	358%
Hydraulic fluid (Iso Grade 32/SAE 10W)	784%	549%	297%	329%
Coolant/antifreeze	945%	786%	368%	410%
Transmission fluid	777%	557%	294%	301%
Gasoline	559%	529%	316%	316%
Diesel	745%	513%	315%	373%
Brake fluid	873%	711%	384%	356%
Rubbing alcohol	663%	530%	312%	312%
Corn syrup	1050%	933%	840%	560%
Honey	1771%	919%	613%	574%
Olive oil	814%	585%	312%	323%

SUNRISE has combined breakthrough technology with 100% recycled materials to create **TRANSFORM**. This incredibly absorbent material out-performs clay, cellulose, vermiculite, powders, peat-moss and other similar sorbent substances. Ideal for the cleanup of oil, paint, hydraulic fluid, antifreeze/coolant, brake fluid, gasoline and many other commonly still liquids. **TRANSFORM's** unique characteristics allow it to float on water while absorbing dangerous and volatile liquids. Safe and convenient packaging allows for easy storage in any location, including vehicles.

DIRECTIONS: **SUNRISE** proposes various methods of application of **TRANSFORM** to oil spills. For hard surface spills, just apply an adequate amount of **TRANSFORM** to the spill and stiff nylon broom the mixture back and forth, then sweep the residue into a dustpan. For water spills, simply spread **TRANSFORM** onto floating oil and lightly agitate. Due to its buoyant, water-resistant qualities, **TRANSFORM** will bond to the waterborne oil spill and congeal into a solid or 'biscuit' and is then easily removable by skimming with a strainer, leaving clean water.



800-648-1153 ~ P.O. BOX 10207 RENO NV, 89510

WWW.SUNRISENV.COM

"LIKE US" ON FACEBOOK FOR EXCLUSIVE SPECIALS AND DISCOUNTS

