

# RUSTY

HEAVY-DUTY RUST REMOVER  
REMOVEDOR DE ÓXIDO

**RUSTY** is designed to remove rust from all metal surfaces with ease. Apply **RUSTY** full strength or dilute with water according to the rust build-up or your required speed of operation. **RUSTY** is an excellent releasing agent for removal of dried on chemicals such as: sulphur, lime, and many other farm chemicals. When diluted with water it can be used to shine soft metals like brass and aluminum. **RUSTY** can also be used to remove cement from mixers and equipment.

## DIRECTIONS

### • WEAR PROTECTIVE EQUIPMENT •

Face shield, chemical resistant gloves, apron and boots.  
**Spray Method:** Spray large items such as: LP gas tanks, fertilizer equipment, antique autos, trucks etc. **RUSTY** will remove rust without removing painted surface. When you've removed the rust, rinse well with water, then paint. **RUSTY** also removes rust from cement. **Dip Method:** Dip rusty metal items such as: nuts, bolts, chain drives, pipes or other small objects until rust is removed, usually a few hours. Rinse well with water, then coat with ALL FREE II, to prevent further rusting.

**CAUTION: CONTAINS STRONG ACID  
HARMFUL OR FATAL IF SWALLOWED. DO NOT GET  
IN EYES, ON SKIN OR ON CLOTHING. PROLONGED  
OR REPEATED EXPOSURE MAY CAUSE DERMATITIS  
IN SENSITIVE INDIVIDUALS. CAUTION: CONTAINS  
STRONG ACID**

**HARMFUL OR FATAL IF SWALLOWED. DO NOT GET  
IN EYES, ON SKIN OR ON CLOTHING. PROLONGED  
OR REPEATED EXPOSURE MAY CAUSE DERMATTI-  
TIS IN INDIVIDUALS.**

## PACKAGING

- 1 Gallon     15 Gallon     275 Gallon  
 5 Gallon     30 Gallon     Other:  
 6 Gallon     55 Gallon

## TRANSPORT INFORMATION

U.N. Number: UN 1789  
U.N. Proper Shipping Name: Hydrochloric Acid  
Transport Hazard Class(es): 8  
Packing Group: II

**SUNRISE**  
ENVIRONMENTAL SCIENTIFIC  
Blending the Demands of Industry and Environment

# RUSTY

## HEAVY-DUTY RUST REMOVER

### PART #2127

READ ENTIRE LABEL BEFORE USING  
KEEP OUT OF REACH OF CHILDREN

## CAUTIONS

Contains caustic and/or strongly alkaline substances, harmful or fatal if swallowed. Avoid contact with eyes, skin and clothing. Prolonged or repeated contact may cause dermatitis in sensitive individuals. Protective equipment recommended. Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent, cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

## INGREDIENTS

\*Hydrochloric Acid 7647-01-0, Ethylethylene Oxide 75-21-8, Liner Alkibenzene Sulfonate Acid 68584-22-5

## HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity:3 Fire: 0 Reactivity: 1 Special: N.A

## Hazard Symbol(s)



For additional information including SDS and Tech Data Sheet scan QR code here →



## California Proposition 65



WARNING this product can expose you to chemicals including diethanolamine, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more info go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

# DANGER: POISON!



PO BOX 10207  
RENO NV, 89510

Since 1975