# **HYDROFOIL**

INSTANT ODOR CONTROL CONTROL INSTANTANEO DELOLOR

### **DIRECTIONS**

### SHAKE WELL BEFORE USING!!

PORTA-TOILETS: Add 1 gallon (4 guarts) directly and cover the solids with water to aid digestion. Every time the toilet is pumped, start treatment again with 1 gallon of product.

RECREATIONAL VEHICLES AND BOATS: Add 2 oz. per gallon of water in holding tank. Thereafter, use 1 oz. per gallon as needed. For use at a dump station, add 1 gallon per 50 gallons of tank capacity. Then use 1 pint per week for maintenance.

SEPTIC TANKS: Add 1 pint per 25 cu. feet capacity for the initial treatment. Thereafter, use 8 oz. per week. This may be poured directly into a toilet and flushed. If septic tank has become clogged and odorous, add 1 gallon of product directly to the tank through the manhole. URINALS AND URINAL TRAPS: Spray on urinal and add 1/4 cup to each drain daily until odorless.

GREASE TRAPS: For traps less than 20 cu. feet capacity, add 4-5 oz. of product daily by pouring in a sink or pipeline closest to the trap. This should be done at night or when the traps are used the least. After adding, flush down with a cup of lukewarm water. For grease traps larger than 20 cu. feet, add 8-10 oz. daily using the same procedure. DRAIN LINES AND DOWN PIPES: Use product a minimum of 2 times weekly to maximum of 4 times depending on the usage of the building. Add product in amounts listed below by pouring directly into the drain pipe starting on the lowest floor and working up at the rate of one floor every day. Do not treat the same floor twice. When the top floor is reached, continue treatment from the top floor only.

### PIPE SIZE DOSAGE FREQUENCY

2"	4 oz.	2 times per week
4"	8 oz.	2 times per week
6"	12 oz.	2 times per week
8"	16.07	2 times per week

WASTE CLEANUP AND REMOVAL OF ODORS FROM CARPET-ING, ETC.: Dilute at the rate of 1 part concentrate to 3 parts water. Saturate area of spill after cleaning area well. Keep area wet for 24 hours. Clean area as usual after this period of time. If odor returns, repeat procedure using a 1 to 1 dilution rate.

### PACKAGING

☐ 1 Gallon	15 Gallon	275 Gallor
○ 5 Gallon	○ 30 Gallon	Other:
○ 6 Gallon	○ 55 Gallon	

## TRANSPORT INFORMATION

U.N. Number: NOot applicable

U.N. Proper Shipping Name: Liquid Cleaner Class 55
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable





# **PART #2093**

READ ENTIRE LABEL BEFORE USING KEEP OUT OF REACH OF CHILDREN

### CAUTIONS

Contains caustic and/or strongly alkaline substances, harmful or fatal if swallowed. Avoid contact with eyes, skin and clothing. Prolonged or repeated contact may cause dermatitis in sensitive individuals. Protective equipment recommended. Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent; cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

### INGREDIENTS

Viable Bacteria Cultures N/A. Tetraacetic Acid 64-02-8. Ethoxylated Alcohol 78330-21-9, Alkyl Benzene Sulfonic Acid 27176-87-0, Alkyl Sulfate 2235-54-3, Sodium Xylene Sulfonate 1300-72-7

### HAZARDS IDENTIFICATION

Signal Word: WARNING

Precautionary Statement(s):

- · Skin and eve irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

### H.M.I.S.

Toxicity: 0 Fire: 0 Reactivity: 0 Special: N.A

### Hazard Symbol(s)



or additional information including SDS and Tech Data Sheet scan QR code here



