

SAFETY SECTION

WARNING: DO NOT INGEST. RESPIRATORY TRACT IRRITANT. MAY CAUSE SKIN IRRITATION OR BURN.

SCAN FOR SDS
& INFORMATION



TOXICITY	1
FIRE	2
REACTIVITY	1
SPECIAL	

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.



LIMITED QUANTITY

Ingredients: Isoparaffinic Hydrocarbon 64742-47-13, Aliphatic Petroleum Distillates 64742-47-8/64742-96-7, Propellant 68-476-86-8, Mineral Oil 647742-52-5

SUGGESTED USES:

- **Bolts and Nuts**
- **Lock Mechanisms**
- **Speedometer**
- **Brake Cables**
- **Fittings**


SUNRISE
ENVIRONMENTAL SCIENTIFIC
Blending the Demands of Industry and Environment

ALL FREE II

PENETRATING LUBRICANT

ALL FREE II

SHAKE WELL BEFORE USING!!

ALL FREE II has a unique combination of ingredients that markedly reduce surface tension which permits rapid, deep penetration of corroded parts. **ALL FREE II**'s unique spray head permits spraying from any angle, allowing penetrant to reach areas otherwise inaccessible. **ALL FREE II** has an affinity to metal which aids penetration. Residual oil film lubricates and provides protection against subsequent corrosion. Penetrates and frees rusty parts such as bolts, nuts, lock mechanisms, speedometers, brake cables, fittings, etc. Helps eliminate the use of cold chisels, torches or saws. **ALL FREE II** has instant action that will cut rust, tar, gum, dirt, grease and corrosion.

DIRECTIONS: Spray **ALL FREE II** on object, saturate rusted or corroded area. Allow **ALL FREE II** to stand for several minutes. If necessary, tap fitting lightly and in extremely difficult cases of frozen parts re-apply as needed.

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

PRODUCT #1068 NET WEIGHT: 16 OZ (455 g)

SUNRISE ENVIRONMENTAL SCIENTIFIC

800-648-1153

PO BOX 10207

RENO, NEVADA 89510



Proudly made
in the USA!



WWW.SUNRISENV.COM