

	TOXICITY 1
scan For s & informat	FIRE 3
	REACTIVITY 1
	SPECIAL

CAUTION: The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120oF. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.



LIMITED QUANTITY

Ingredients: Methylal 109-87-5, Isopropyl Alcohol 67-63-0, Isopropyl Hydrocarbon 64742-47-13, Carbon Dioxide 124-38-9

FEATURES:

- Removes: Oil, Grease, flux and other contaminates
- Ideal in sensitive cleaning situations





CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING. KEEP OUT OF REACH OF CHILDREN PRODUCT #1031 NET WEIGHT: 12 OZ (340 g)

PHAZER II

An ultimate purity, non-hazardous spray specially formulated for removing oil, grease, flux and other contaminants from sophisticated electronic parts. **PHAZER II** leaves no residue. **USAGES**: Control panels, tuners, printed circuit boards, terminals, relay switches, contacts and electronic equipment.

DIRECTIONS:

PHAZER II may be harmful to certain plastics. Pre-test plastic or painted components in an inconspicuous area before using. Disconnect power source prior to application. Flush surface with **PHAZER II** and allow to run off. **PHAZER II** dries film-free quickly. For hard-to-reach areas, use extension tube provided.

USE ON:

- Control Panels
- Tuners
- Terminals
- Circuit Boards
- Other Electrical Equipment

SUNRISE ENVIRONMENTAL SCIENTIFIC



