RELEASE 250

HEAVY-DUTY SYNTHETIC SHAKER PAD LUBRICANT Lubricante Para Gomas De Extractor De Frutos

RELEASE 250 is a clear, non-toxic silicone spray lubricant designed to lubricate and protect rubber tree-shaker slings. This compound deeply penetrates into rubber and leaves a stable broadcast of silicone to provide a slippery barrier for reduced friction on the rubber to rubber surface. It prevents heat build-up during the tree shaking operation and prevents bark damage to the tree. This clean, non-toxic formula can be used with confidence to provide solutions to a multitude of lubrication problems associated with valves, pistons, rings, seals, slides, tracks, hinges, gears, etc.

DIRECTIONS

Point trigger toward target area and spray a thin film into the working surface of the shaker sling. As the lubricant impregnates the surface of the rubber, a shiny wet appearance will be maintained. Re-apply approximately once per hour or as conditions warrant.

When new shaker slings are installed it is recommended to pre-soak the working surface of the rubber with RELEASE 230 two or three times at 1-hour intervals prior to installation.

For additional information including SDS and Tech Data Sheet scan QR code here



FEATURES:

- Deeply Penetrates for Reduced Friction
- Safe on Trees
- No Harsh Solvent
- Silicone Blend

SUGGESTED USES:

- Shaker Slings
- Valves and Pistons
- Rings. Seals. Gear Tracks. Hunges. Etc





PRODUCT #1124 NET WEIGHT: 16 OZ (454 g)

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMEUL READ CAUTIONS ON BACK PANEL BEFORE USING

KEEP OUT OF REACH OF CHILDREN

CAUTIONS

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.

INGREDIENTS

Polyetherafluorethane 9002-84-0, Mineral Oil Food Grade 64742-52-5, Aliphatic Petroleum Distillate 64742-89-8, Hydrocarbon Propellant 68-476-86-8

HAZARDS IDENTIFICATION

Signal Word: WARNING

Precautionary Statement(s):

- Skin and eye irritant
- · Respiratory tract irritant
- · Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity: 1 Fire: 3 Reactivity: 0 Special: N.A

Hazard Symbol(s)



TRANSPORT INFORMATION

U.N. Number: UN 1950 U.N. Proper Shipping Name: Aerosol, Flammable Transport Hazard Class(es): 2.1 Description: UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

SUNRISE ENVIRONMENTAL SCIENTIFIC 800-648-1153 SUNRISENV.COM





PO BOX 10207 RENO NV, 89510

Since 1975