

## MAGIC GLIDE

Silicone lubricant  
Lunricante de silicona

SUNRISE' MAGIC GLIDE is a non-staining, stable blended formula that deeply penetrates, thus eliminating sticking problems and annoying squeaks. MAGIC GLIDE will repel water and ice and retard rust and corrosion. It will lubricate and free sticking windows, doors, drawers, zippers, cabinets, etc. Also, may be used on rubber, leather, metal, nylon, wood and painted surfaces. MAGIC GLIDE is excellent for use on municipal vehicles to eliminate fan belt and rubber squeaks, freezing doors, and metal noises in addition to waterproofing electrical connections and ignition systems.

### DIRECTIONS

Shake container well.

For additional information including SDS and Tech Data Sheet scan QR code here →



### FEATURES:

- Non-Staining
- Repels water and Ice
- Prevents sticking and squeaking

### SUGGESTED USES:

- Doors
- Hinges
- Equipment
- Tracks
- Waterproofing



# MAGIC GLIDE

## SILICONE LUBRICANT

PRODUCT #1034

NET WEIGHT: 13.4 OZ (382 g)

**CAUTION:** CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

**KEEP OUT OF REACH OF CHILDREN**

### CAUTIONS

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician. Consult Safety Data Sheet for additional information.

### INGREDIENTS

Aliphatic Hydrocarbon 64742-47-8, Isoparaffinic Hydrocarbon 64742-47-13, Polydimethylsiloxane Silicone 63148-62-9, Hydrocarbon Propellant 68-476-86-8, Benzene 71-43-2

### HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

### H.M.I.S.

Toxicity: 1 Fire: 3 Reactivity: 0 Special: N.A

### Hazard Symbol(s)



### TRANSPORT INFORMATION

U.N. Number: UN 1950

U.N. Proper Shipping Name: Aerosol, Flammable

Transport Hazard Class(es): 2.1

Description: UN 1950, Aerosols, Flammable, 2.1, Limited Quantity



**WARNING:** This product can expose you to chemicals including Diethanolamine, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**SUNRISE ENVIRONMENTAL SCIENTIFIC**

800-648-1153 SUNRISENV.COM



PO BOX 10207  
RENO NV, 89510

*Since 1975*