

STEAMEZE

DESIGNED FOR HIGH PRESSURE STEAM EQUIPMENT
ELIMINA LA ORINA, LA ESCALA Y LA ACUMULACIÓN

STEAMEZE quickly removes oil, grease and dirt from metal and concrete surfaces. The special penetrants in STEAMEZE assure a clean surface ready for painting. Do not use full strength on aluminum alloys.

DIRECTIONS:

Set meter to 1 gallon of STEAMEZE to 20 gallons of water. Adjust nozzle for best results. May cause damage to non-ferrous metals and painted surfaces in concentrated form.

For additional information including SDS and Tech Data Sheet scan QR code here →



PACKAGING

- 1 Gallon 15 Gallon 275 Gallon
 5 Gallon 30 Gallon Other:
 6 Gallon 55 Gallon

TRANSPORT INFORMATION

U.N. Number: Not applicable
U.N. Proper Shipping Name: Limited Quantity Class 85
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable



STEAMEZE

DESIGNED FOR HIGH PRESSURE STEAM EQUIPMENT

PART #2046

READ ENTIRE LABEL BEFORE USING
KEEP OUT OF REACH OF CHILDREN

CAUTIONS

Contains caustic and/or strongly alkaline substances, harmful or fatal if swallowed. Avoid contact with eyes, skin and clothing. Prolonged or repeated contact may cause dermatitis in sensitive individuals. Protective equipment recommended. Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent, cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

INGREDIENTS

Sodium Hydroxide 1310-73-2, Sodium Metasilicate 6834-92-0, Sodium Gluconate 7-1-0527, Nonylphenol Ethoxylate 9016-45-9, Sodium Xylenesulfonate 1300-72-7, Sodium Polyacrylate

HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity: 2 Fire: 0 Reactivity: 1 Special: N.A

Hazard Symbol(s)



PO BOX 10207
RENO NV, 89510

Since 1975