

NOT FOR RESALE



SUNRISE

ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

RELEASE 212

SILICONE LUBRICANT STOPS STICKING

LUBRICANTE DE SILICONA

**READ ENTIRE LABEL BEFORE USING.
KEEP OUT OF REACH OF CHILDREN**

SAFETY SECTION

SCAN FOR
SDS & INFO



TOXICITY 1

FIRE 3

REACTIVITY 0

SPECIAL NA



DANGER

- SKIN AND EYE IRRITANT
- RESPIRATORY TRACT IRRITANT
- SWALLOWING WILL CAUSE GASTRO-INTESTINAL IRRITATION



Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent; cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least

15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

Ingredient Name	CAS#
Aliphatic Petroleum Distillate	64742-89-8
Isoparaffinic Hydrocarbon	64742-47-13
Benzene	71-43-2



WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

PRODUCT #2076• BATCH #

TO REORDER CALL US @ 800.648.1153

RELEASE 212, a non-staining, siliconized lubricant in a stable formula that deeply penetrates, thus eliminating sticking problems and annoying squeaks. RELEASE 212 will repel water and ice and retard rust and corrosion. RELEASE 212 will lubricate and free-up sticking windows, doors, drawers, zippers, cabinets, etc. Also, RELEASE 212 may be used on rubber, leather, vinyl, metal, nylon, wood and painted surfaces. Excellent for use on municipal vehicles to eliminate fan belt and rubber squeaks, freeing doors, and metal noises in addition to waterproofing electrical connections and ignition systems.

DIRECTIONS

Apply RELEASE 212 to object; saturate rusted or corroded area. Allow RELEASE 212 to stand for several minutes. If necessary, tap fitting lightly, and in extremely difficult cases of frozen parts, re-apply as needed.

CAUTION: Do not use near fire or flame. Use ventilation adequate to maintain TLV. Avoid contamination of food or potable water. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

SHIPPING/ DOT CLASSIFICATION

UN 1268, PETROLEUM DISTILLATES, N.O.S. (CONTAINS NAPHTHA SOLVENT), 3, PG II, CLASS 70

SUNRISE ENVIRONMENTAL SCIENTIFIC



800-648-1153 SUNRISENV.COM
PO BOX 10207 - RENO, NEVADA 89510