CABLE CLEAN

REMOVES CORROSION AS IT CLEANS AND PROTECTS

CABLE CLEAN penetrates dirt, grime and corrosion instantly. Seals battery surface and allows battery to be kept in the best of condition in or out of storage.

DIRECTIONS:

After removing all excess corrosion by wiping, rinsing or brushing terminals, spray SUNRISE' CABLE CLEAN on, Wait 2-3 minutes. wipe clean or rinse. Spray batteries with a light application for lasting protection.

For additional information including SDS and Tech Data Sheet scan QR code here




SUGGESTED USES:

- Cars
- Trucks
- ATVs
- Chrome
- Machinery
- Equipment



Blending the Demands of Industry and Environment



PRODUCT #1046 **NET WEIGHT: 14 OZ (396 g)**

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

CAUTIONS

The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Avoid prolonged or repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Point tip away from body and eyes before spraying. Do not spray near open flame or ignition source. Avoid contamination of food or potable water. Dispose of empty can in accordance with local regulations. Do not ingest. If skin is contacted, wash off with soap and water. If eyes are contacted, flush 15 minutes with water. See a physician, Consult Safety Data Sheet for additional information

INGREDIENTS

Propellant 68-476-86-8, Nonelphenol Ethoxlate 9016-45-9. Sodium Bicarbonate 144-55-8. Sodium Nitrite 7632-00-

0. Sodium Benzoate 5321-32-1

HAZARDS IDENTIFICATION

Signal Word: WARNING

Precautionary Statement(s):

- · Skin and eye irritant
- · Respiratory tract irritant
- · Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity: 0 Fire: 0 Reactivity: 0 Special: N.A

Hazard Symbol(s)



SUNRISE ENVIRONMENTAL SCIENTIFIC SUNRISENV.COM 800-648-1153







Since 1975