

LIGHTNING FG UNSCENTED

FOOD GRADE SILICONE LUBRICANT
LUBRICANTE DE SILICONA CON GRADO ALIMENTICIO

LIGHTNING FG UNSCENTED is a non-staining, stable blended formula that deeply penetrates, thus eliminating sticking problems and annoying squeaks. **LIGHTNING FG UNSCENTED** will repel water and ice and retard rust and corrosion. It will lubricate and free sticking windows, doors, drawers, zippers, cabinets, etc. Also, may be used on rubber, leather, metal, nylon, wood and painted surfaces.

NOTE:

This product contains a solution of saturated aliphatic hydrocarbons. Addition to food not to exceed 1 part per million. The silicone ingredient is in the code of Federal Regulations of the FDA, in 21 CFR part 178.3570.


For additional information including SDS and Tech Data Sheet scan QR code here →



Nonfood Compounds
Program Listed (H1)
REG #145311

PACKAGING

- 1 Gallon 15 Gallon 275 Gallon
 5 Gallon 30 Gallon Other:
 6 Gallon 55 Gallon



SUNRISE
ENVIRONMENTAL SCIENTIFIC
Blending the Demands of Industry and Environment

UNSCENTED
LIGHTNING FG
FOOD GRADE SILICONE LUBRICANT

PART #2239

READ ENTIRE LABEL BEFORE USING
KEEP OUT OF REACH OF CHILDREN

CAUTIONS

Contains caustic and/or strongly alkaline substances, harmful or fatal if swallowed. Avoid contact with eyes, skin and clothing. Prolonged or repeated contact may cause dermatitis in sensitive individuals. Protective equipment recommended. Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

INGREDIENTS

Silicon Emulsion 63148-62-9, Isoparaffinic Hydrocarbon

HAZARDS IDENTIFICATION

Signal Word: **WARNING**

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity: 1 Fire: 2 Reactivity: 0 Special: N.A

Hazard Symbol(s)



PO BOX 10207
RENO NV, 89510

Since 1975