

NOT FOR RESALE



SUNRISE

ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

G-FORCE

PAINT REMOVAL COMPOUND

REMOVEDOR DE PINTURA

**READ ENTIRE LABEL BEFORE USING.
KEEP OUT OF REACH OF CHILDREN**

SAFETY SECTION

SCAN FOR
SDS & INFO



TOXICITY 1

FIRE 2

REACTIVITY 1

SPECIAL NA



WARNING

- SKIN AND EYE IRRITANT
- RESPIRATORY TRACT IRRITANT
- SWALLOWING WILL CAUSE GASTRO-INTESTINAL IRRITATION



Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

Ingredient Name	CAS#
Citrus Distillate	68647-72-3
Di-BasicEster	1119-40-0
Distillates, hydrotreated light	64742-47-8
Benzene	71-43-2
*Aliphatic Glycol Ether	112-34-5



WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

PRODUCT #2149 • BATCH #

TO REORDER CALL US @ 800.648.1153

G-FORCE was formulated for the easy removal of paint, primarily from walls and concrete. G-FORCE is designed to remove paint from bridge abutments, street signs, walls, sidewalks, etc.

DIRECTIONS

Use G-FORCE in a well-ventilated area. If necessary, use a mechanical ventilating device or move the target surface to another area. Pre-test an inconspicuous spot for color fastness prior to use. Spray or roll on the surface to be cleaned, allow it to act a few seconds, then wipe off with a clean cloth or rinse with a garden hose or pressure washer. For best results it is recommended that you use a pressure washer. For marks difficult to remove, repeat the application allowing G-FORCE to act on the surface for a longer time. For porous surfaces scrub the area with a stiff bristle brush after spraying and then wipe off or rinse with water.

SHIPPING/ DOT CLASSIFICATION

LIQUID CLEANER CLASS 55

SUNRISE ENVIRONMENTAL SCIENTIFIC



800-648-1153 SUNRISENV.COM
PO BOX 10207 - RENO, NEVADA 89510