NOT FOR RESALE

SUNRISE

ENVIRONMENTAL SCIENTIFIC

Blending the Demands of Industry and Environment

SUMMIT

CONCENTRATED ODOR CONTROL

READ ENTIRE LABEL BEFORE USING. KEEP OUT OF REACH OF CHILDREN

SAFETY SECTION

SCAN FOR SDS & INFO TOXICITY ()
FIRE 2

REACTIVITY 1
SPECIAL IV:



DANGER

- FATAL OR TOXIC IF SWALLOWED
 RESPIRATORY TRACT IRRITANT
 MAY CAUSE SKIN BURN OR EYE
- DAMAGE

Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting, Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent; cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush

tion adequate to prevent; cough, hoarseness, or irritation. Data approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately, if skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediatly. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

Ingredient Name	CAS#
Isopropyl Alcohol	67-63-0
Deodorant (proprietary)	N/A
Methyl Saliclyate	068917-75-9

FEATURES AND BENEFITS

- SAFE FOR LAND APPLICATION
- UNIQUE NEUTRALIZER
- CONTAINS NO O.D.B.
- ELIMINATES FOUL ODORS

PRODUCT # 2006 • BATCH #

TO REORDER CALL US @ 800.648.1153

SUMMIT is especially formulated for controlling odors in Sewage Disposal Plants, Lagoons, Sludge Drying Beds, Drainage Ditches. Aerators, Land Fills, Refuse Dumps, Sewer Mains, Storm Sewers, Wet Wells, Lift and Pumping Stations, Garbage Dumps and Trucks. For municipal, professional and industrial use only.

DIRECTIONS

DIRECTIONS: For sewer drip applications, use 1 gallon per 250,000 to 1,000,000 gallons of sewage flow.

For mist applications over large areas, use 1 gallon of product in 100 to 200 gallons of water. Spray over area of desired odor control.

For long-lasting odor control of contaminated or highly odiferous areas, a lower dilution rate may be necessary

SHIPPING/ DOT CLASSIFICATION

UN 1219, ISOPROPANOL, 3, PG II, CLASS 70

SUNRISE ENVIRONMENTAL SCIENTIFIC



800-648-1153 SUNRISENV.COM PO BOX 10207 - RENO, NEVADA 89510