

SAFETY SECTION

DANGER: FATAL OR TOXIC IF SWALLOWED. RESPIRATORY TRACT IRRITANT. MAY CAUSE SKIN IRRITATION OR BURN.

SCAN FOR SDS
& INFORMATION



| | |
|-------------------|----------|
| TOXICITY | 2 |
| FIRE | 3 |
| REACTIVITY | 0 |
| SPECIAL | |

CAUTION: The contents of this container are under pressure. Do not puncture or incinerate. Do not store in direct sunlight or where temperature exceeds 120°F. Use ventilation adequate to maintain TLV. Point tip away from body and eyes before spraying. Avoid contamination of food or potable water. Do not ingest. If eyes are contacted flush with water for 15 minutes. Consult Safety Data Sheet for further information.



LIMITED QUANTITY

Ingredients: Acetone 67-64-1, Propellant 68-476-86-8, Isoparaffinic Hydrocarbons 64742-47-13, Polytetrafluoroethylene 9002-84-0, White Mineral Oil 8042-47-5

FEATURES

- Long lasting “DRY” lubricant
- High Temperature Range (500°F)
- Durable
- Dries quickly



TEFLUBE

SPECIALTY DRY LUBRICANT AND RELEASE

CAUTION: CONTENTS UNDER PRESSURE. VAPOR MAY BE HARMFUL. READ CAUTIONS ON BACK PANEL BEFORE USING.

KEEP OUT OF REACH OF CHILDREN

PRODUCT #1024 NET WEIGHT: 17.5 OZ

TEF-LUBE

SUNRISE' miracle product will make short work of your tasks. Look at these advantages:

*Long Lasting **DRY** Lubricant
Works Up To 500°F.
Dries Quickly
Can Be Removed With Toluene*

DIRECTIONS:
SHAKE VIGOROUSLY BEFORE
EACH USE.

Apply to a clean surface. Hold container 5 to 10 inches from surface and spray a thin film on area to be treated. If spraying on or near plastics test on inconspicuous area for solvent compatibility.

USE ON

- Chains
- Tools
- Rails
- Slide Tables
- Nearly any moving part

SUNRISE ENVIRONMENTAL SCIENTIFIC

800-648-1153

PO BOX 10207

RENO, NEVADA 89510



Proudly made
in the USA!



WWW.SUNRISENV.COM