# Blending the Demands of Industry and Environment

# **REMOVES URINE, SCALE, AND BUILD-UP**

ELIMINA LA ORINA, LA ESCALA Y LA ACUMULACIÓN

READ ENTIRE LABEL BEFORE USING. KEEP OUT OF REACH OF CHILDREN

# SAFETY SECTION



TOXICITY 3
FIRE 0
REACTIVITY 1

SPECIAL N

### DANGER

•SKIN AND EYE IRRITANT
•RESPIRATORY TRACT IRRITANT
•MAY CAUSE SKIN BURN OR EYE
DAMAGE



Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent; cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediatly. Flush with large amounts of water. Wash in an automatic machine

before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

### Ingredient Name CAS #

 Sodium Hydroxide
 1310-73-2

 Potassium Hydroxide
 1310-58-3

 "2 Butoxyethanol
 111-76-2

 "2 Diethylene Glycol
 111-90-0

 Diethanolamine
 111-42-2

Diethanolamine Monoethyl Ether Sodium Xylenesulfonate Coco Diethanolamide Nonylphnol Ethoxylate

N/A 1300-72-7 86603-42-9 127087-87-0 6834-92-0



WARNING: This product can expose you to chemicals including Diethanolamine, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

PRODUCT #2174 • BATCH #

### TO REORDER CALL US @ 800.648.1153

**SCALE-X** is the ultimate in cleaning the most stubborn stains prone to the portable toilet industry. **SCALE-X** is designed to remove urine and scale build-up as well as the heaviest dirt and grease stains common to the industry. **SCALE-X** works great with the use of a pressure washer and as a pre-soak for the heaviest of stains.

### **DIRECTIONS**

Dilute 1 part **SCALE-X** to 30 parts water for light-duty cleaning. For those hard jobs, dilute 1 part **SCALE-X** to 20 parts water. Different soil conditions may require heavier concentrations. **NOTE:** Not for use on aluminum and other non-ferrous metals. May cause etching on these metals.

# SHIPPING/ DOT CLASSIFICATION

UN 1824, SODIUM HYDROXIDE SOLUTION, 8, PG III CLASS 85

## SUNRISE ENVIRONMENTAL SCIENTIFIC



800-648-1153 SUNRISENV.COM PO BOX 10207 - RENO, NEVADA 89510