PA-25

REMOVES ALL FORMS OF CONCRETE FROM METAL SURFACES

REMOVEDOR CONCRETO

PA-25 will remove hardened cement from handling equipment such as bulk cement haulers, redimix equipment, cement mixers and locations in cement manufacturing plants.

DIRECTIONS

PA-25 should be diluted; 1 part with 2 parts water. Apply solution to surface to be cleaned. After foaming action stops, flush with water. Reapply if build-up is excessive. Before using PA-25, it is recommended that surfaces around and below area to be cleaned should be tested to make sure no harm will result from splashing of this product.

CAUTION: CONTAINS STRONG ACID

HARMFUL OR FATAL IF SWALLOWED, DO NOT GET IN EYES, ON SKIN OR ON CLOTHING, PROLONGED OR REPEATED EXPOSURE MAY CAUSE DERMATTI-TIS IN INDIVIDUALS.

275 Gallon

Other:

PACKAGING

- 1 Gallon 15 Gallon 5 Gallon
 - 30 Gallon
- 55 Gallon ○ 6 Gallon





PART #2018

READ ENTIRE LABEL BEFORE USING KIEEP OUT OF REACH OF CHILDREN

CAUTIONS

Contains caustic and/or strongly alkaline substances, harmful or fatal if swallowed. Avoid contact with eyes, skin and clothing. Prolonged or repeated contact may cause dermatitis in sensitive individuals. Protective equipment recommended. Gloves, apron and goggles recommended. Do not ingest. If ingested drink large quantities of potable water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Use ventilation adequate to prevent; cough, hoarseness, or irritation. OSHA approved respirator recommended. If eyes are contacted, flush with water for at least 15 minutes. See a physician immediately. If skin is contacted, wash off with soap and water. Do not apply ointments until a physician is consulted. Clothing that is contaminated should be removed immediately. Flush with large amounts of water. Wash in an automatic machine before wearing again. Dispose of empty container in accordance with local regulations. Consult Safety Data Sheet for additional information.

INGREDIENTS

*Hydrochloric Acid 7647-01-0, Phosphoric acid 7664-38-2, Ethylene Oxide 75-21-8, Liner Alklbenzene Sulfonate Acid 68584-22-5

HAZARDS IDENTIFICATION

Signal Word: DANGER

Precautionary Statement(s):

- Skin and eye irritant
- Respiratory tract irritant
- Swallowing will cause gastrointestinal irritation

H.M.I.S.

Toxicity: 3 Fire: 0 Reactivity: 1 Special: N.A.

Hazard Symbol(s)







California Proposition 65



VARNING this product can expose you to chemicals including diethanolamine, which is known to the State of California to cause cancer and/or cause birth defects or other reproductive harm. For more info go to www.p65warnings.ca.gov







PO BOX 10207 **RENO NV. 89510**

Since 1975